

tomer and Order Inf	ormation	
ase Order *	Tag	
·/Provider Name *		·
aser Name and Contact Informati	ion *	
ng Address *		
nformation ( <i>if available</i> ) Wei	ight kgs Height cm	* required
e Chair		
T50 Fuze T50 50° Manual Tilt \	Wheelchair	\$
Also available: the narrow <b>F</b>	<b>euze T50n</b> with an overall chair width of seat plus only 4". See separate order form. pdgmob	ility.com/narrow
ne_Type & Weight Ca	apacity	
136kg/300 lbs Weight Capacity		
<u> </u>	Not compatible with Transit Tie Down System. Requires Flat-free Rear Tires or Heavy Duty Spoke Rear Wheels.	
Adjustable Width Frame 1	13kg/250 lbs Weight Capacity. Limited compatibility with Take-Apart Frame. Select an Adjustable Seat Width below.	\$
ne Options		
	Apart frame allows attendants to take the Fuze apart in seconds without tools. pdgmobility.com/take-apart	\$
		*
•		h
Fo	Id ATE Tilt Take	
	apart apart	
FUZE	TAKE-APART Check the PDG Blog for more details.	
FUZE  Transit Tie Down System (TT	TAKE-APART Check the PDG Blog for more details.	
•	TAKE-APART Check the PDG Blog for more details.  TDS)  Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.	
TTDS includes 4 factory-installed train	TAKE-APART Check the PDG Blog for more details.  TDS)  Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.	5" for 20/22/24" RW
TTDS includes 4 factory-installed trained to max. Weight Capacity of 3	TAKE-APART Check the PDG Blog for more details.  TDS)  Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  100 lbs.	5" for 20/22/24" RW
TTDS includes 4 factory-installed train Tested to max. Weight Capacity of 30	TDS)  Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.	5" for 20/22/24" RW
TTDS includes 4 factory-installed transcribed to max. Weight Capacity of 3  Width  Fixed Seat Widths Order w	TAKE-APART Check the PDG Blog for more details.  TDS) Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.  with Fixed Frame.	5" for 20/22/24" RW
TTDS includes 4 factory-installed trained to max. Weight Capacity of 30  Width  Fixed Seat Widths Order w  15" Seat Width	TAKE-APART  Check the PDG Blog for more details.  TDS) Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.  With Fixed Frame.  O3016 16" Seat Width	5" for 20/22/24" RW
TTDS includes 4 factory-installed train Tested to max. Weight Capacity of 3  Width  Fixed Seat Widths Order w  15" Seat Width  18" Seat Width  20" Seat Width  23" Seat Width	TAKE-APART  Check the PDG Blog for more details.  TDS) Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.  with Fixed Frame.  03016 16" Seat Width 03019 19" Seat Width	
TTDS includes 4 factory-installed trained to max. Weight Capacity of 3 and the second	TAKE-APART  Check the PDG Blog for more details.  TDS) Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.  with Fixed Frame.  03016 16" Seat Width 03019 19" Seat Width	\$
TTDS includes 4 factory-installed train Tested to max. Weight Capacity of 3 and a second seco	TAKE-APART Check the PDG Blog for more details.  TDS) Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.  with Fixed Frame.    03016   16" Seat Width   03017   17" Seat Width   03019   19" Seat Width   03021   21" Seat Width   03022   22" Seat Width	\$ \$
TTDS includes 4 factory-installed train Tested to max. Weight Capacity of 3.  Width  Fixed Seat Widths Order w. 15" Seat Width  18" Seat Width 20" Seat Width 23" Seat Width 4 24" Seat Width	TAKE-APART  Check the PDG Blog for more details.  TDS) Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.  with Fixed Frame.  03016 16" Seat Width 03019 19" Seat Width 03021 21" Seat Width 03022 22" Seat Width	\$ \$
TTDS includes 4 factory-installed train Tested to max. Weight Capacity of 3 and a second seco	TAKE-APART Check the PDG Blog for more details.  TDS) Insport brackets. TTDS has been tested according to ANSI/RESNA WC 19. See Owners Manual for complete details.  Overall chair width is +7.5" for 12/16" RW and +8.  with Fixed Frame.    03016   16" Seat Width   03017   17" Seat Width   03019   19" Seat Width   03021   21" Seat Width   03022   22" Seat Width	\$ \$
	/Provider Name * aser Name and Contact Information Address * aformation (if available) Wei  Chair  T50 Fuze T50 50° Manual Tilt V  Also available: the narrow F  Text available: the narrow F  Time Type & Weight Capacity  136kg/300 lbs Weight Capacity  181kg/400 lbs Weight Capacity  181kg/400 lbs Weight Capacity  Take-Apart Frame  The Take- This feature reduces the weight of the Not compatible with Power Tilt, Dru  Take-Apart rear crossbar is not width adjustable width frame (can be order	/Provider Name *  aser Name and Contact Information *  ang Address *  aformation (if available) Weight kgs Height cm  Chair  Too Fuze T50 50° Manual Tilt Wheelchair  Also available: the narrow Fuze T50n with an overall chair width of seat plus only 4". See separate order form. pdgmot  Type & Weight Capacity  Fixed Width Frame Select a Fixed Seat Width below.  136kg/300 lbs Weight Capacity  181kg/400 lbs Weight Capacity  Not compatible with Transit Tie Down System. Requires Flat-free Rear Tires or Heavy Duty Spoke Rear Wheels.  Adjustable Width Frame 113kg/250 lbs Weight Capacity, Limited compatibility with Take-Apart Frame. Select an Adjustable Seat Width below.  Take-Apart Frame The Take-Apart frame allows attendants to take the Fuze apart in seconds without tools. pdgmobility.com/take-apart This feature reduces the weight of the heaviest piece of the wheelchair to 13kg/29 lbs or less. Perfect for transporting it in the boot of a car or SUV. Not compatible with Power Tilt, Drum Brakes, N Pole, O2 Holder, Ventilator Tray, Ventilator Battery Tray, DRB, 13" STF. Take-Apart rear crossbar is not width adjustable. PDG will provide one no-charge crossbar in a different width over the lifetime of each chair ordered with adjustable width frame (can be ordered with the chair or later).







Seat	Depth	
	Standard Seat Depths (Adjustable)	
04015	15" Seat Depth	
04018	18" Seat Depth	
□ 04020	20" Seat Depth	\$
	Custom Seat Depths Requires Stroller Handle Back - Straight. Not compatible with Reclining or Fold-down Back.	
04021	21" Seat Depth	\$
04022	22" Seat Depth	Ś
	·	•
Fram	e Colour	
	PDG Premium Colours View colour swatches on PDG's website. pdgmobility.com/colors	
05001	Black Shimmer $\square$ 05015 Sky Blue $\square$ 05016 Poppy Red	
05003	Fine Texture Black $\square$ 05010 Lollypop Blue $\square$ 05011 Lollypop Red	
05017	Arctic Grey $\square$ 05018 Tropical Teal $\square$ 05019 Tangerine Orange	
05020	Olive Green $\square$ 05021 Lush Lilac $\square$ 05012 Bubble Gum Pink	
05022	Leaf Green $\square$ 05023 Boysenberry Purple $\square$ 05014 Daffodil Yellow	
05200	Custom Colour Contact Permobil for specifications.	\$
Armr	ests	
06000	No Armrests	
_	Height Adjustable Armrests (Single Post)	\$
06114	10"-14" Range	
06100	Fixed Height Armrests (12") Full Length Armpad only.	
عو	Armrest Height If provided, Armrests will be set to this height by PDG. If left blank, the default setting will be used.	
3	Seat Pan to top of Armrest: Does not include height of Armpad	
3ª	Armrest Position Indicate preference for Armrest position. If left blank, the default setting will be used.	
	In the interest of maintaining chair stabily and avoiding interferance with other chair functions, PDG may not be able to accommodate stated preference.	
06402	Mid 06403 Front	
	<b>Locking Flip-up Armrests</b> Not recommended for users with excessive strength or tone. Not compatible with Fold-down Back.	\$
06310	Set at 10"	
06313	Set at 13"	
Armp	oads	
AT III P		
	Regular Armpads	
□ 07100	5	
	Waterfall Armpads	\$
U 07105	5	
	Wide Armpads May interfere with wheels in some tilt configurations.	\$
U 07110	3	
	Gel Armpads May interfere with wheels in some tilt configurations.	\$
07120	Full Length - 2" x 12"	
	Contour Arm Trough with Hand Pad	\$
	Not compatible with Lap Tray, Locking Flip-up Armrests. May interfere with wheels in some tilt configurations.	
☐ 07130	Right (4.5" x 18")	
A r m r	est Options	
	Armrest Wideners Move Armrests outward by up to 1" on each side. Seat size does not change.	
07210	1" Total Additional Width	\$
07210	2" Total Additional Width	¢



<i>c</i> .		
	t Pan	
U 08000	No Seat Pan	
08001	OI Solid Aluminium Seat Pan	\$
Seat	t Height	
_ Don't		
forget		1
	RW 13" 14" 15" 16" 17" 18" 19" 20" RW 13" 14" 15" 16" 17" 18" 19" 20"	
	12"	
	16"	
	20"	
	24" Low STF	
	CII Carteria O Oli Farda	· 1
	6" Casters & 8" Forks 8" Casters & 8" Forks 8" RW 13" 14" 15" 16" 17" 18" 19" 20" RW 13" 14" 15" 16" 17" 18" 19" 20"	
	12"   Std. STF	
	16"	
	20"	
	22"	
		I
	Frog Legs 6" Soft Roll & Suspension Forks	
	RW 13" 14" 15" 16" 17" 18" 19" 20"	
	16"	
	20"	
	22"	
	24" Low STF	
Caste	ters	
	Urethane Casters	
☐ 11051	51 5" x 1.25" Caster size	
	63 6" x 1.50" Caster size	\$
	84 8" x 2.00" Caster size	\$
	Pneumatic Casters	
11161	61 6" x 1.25" Caster size	\$
11181	81 8" x 1.25" Caster size	\$
□ 11184	84 8" x 2.00" Caster size	\$
11260	60 Frog Legs 6" x 1.50" Aluminium Soft-Roll Casters	\$
11400		\$
Rear	r Wheels	
	Composite Wheels	
12012		
12022		
	Spoke Wheels	\$
12120		
12224	24" Heavy Duty Spoke Wheels	\$
4	Rear Wheel Position Indicate Rear Wheel positioning preference. If left blank, the default setting will be used.	
12401	In the interest of maintaining chair stabily and avoiding interferance with other chair functions, PDG may not be able to accommodate stated prefe 01 Rear More stable	rence.
12401	or near more stable	







Axle	Туре									
13000	Quick Release Rear Axles									
13010	Fixed Rear Axles									
Door	Timos									
_	Tires									
	Urethane Tires									
14010	Pneumatic Tires May result in a finished Seat Height 1/2" greater than stated.	\$								
14020	Pneumatic Tires with Flat-Free Inserts May result in a finished Seat Height 1/2" greater than stated. Not available with Spoke Wheels.	\$								
Hand	rims Handrims are available only with 20", 22", and 24" Rear Wheels.									
15000	No Handrims									
15010	Standard Aluminium Handrims									
15020	Plastic Coated Handrims Not compatible with Drum Brakes.	\$								
15030	Projection Handrims Composite Wheels only. 10 Projections, 30°, 1-1.8" Length.	\$								
\// b = =	l Laglage Dualing									
w n e e	el Locks & Brakes									
☐ 16010	User Wheel Locks									
	Push to Lock									
	Attendant Wheel Locks (Push to Lock) Not compatible with Drum Brakes, Wheel Lock Extensions.	\$								
_	User & Attendant Wheel Locks Not compatible with Drum Brakes.  Not compatible with Drum Brakes.	\$								
_	Foot Operated Wheel Lock Rear-mounted unilateral single-activation lock. Not compatible with O2 Holder, IV Pole, Ventilator Tray, One-ArmDrive.	\$								
LJ 16300	<b>Drum Brakes</b> Available with 12" Composite or 20" Spoke Rear Wheels. Urethane Tires only.  12" Wheels compatible with 13" 14" 17.5" 18.5" 19.5" STE Height only. 20" Wheels compatible with 16", 17" 18" STE Height only.	\$								
	12" Wheels compatible with 13", 14", 17.5", 18.5", 19.5" STF Height only. 20" Wheels compatible with 16", 17", 18" STF Height only.  User-activated Unilateral Wheel Lock Pull to Lock. Availlable up to 22" Seat Width only.									
16310										
\// b = =	llock Ontions									
	el Lock Options									
L 16100	Wheel Lock Extensions Not compatible with Attendant Wheel Lock.	\$								
Anti-	Tippers									
<b>X</b> 17010	Rear Anti-Tippers Required Safety Option.	\$								
Back	Posts									
	Back Post Style									
18100	Stroller Handle Back									
	Back Post Type									
18200										
☐ 18420	Back Post Height Measured from the Seat Pan to the Handle.  Short (17") □ 18425 Tall (23")									
L 18420	Back Post Folding Fold-down Back is not compatible with Dynamic Rocker Back Interface, Reclining Backrest.									
☐ 19220	Fold-down 19221 Non-folding									
	Seat to Back Angle									
19090	Set at 90°									
19108	Set at 114°									



D a ck	Ontions								
Васк	Options	Ś							
	Angle/Height Adjustable Stroller Handle Not compatible with Headrest Mounting Plate or Cane Handle Back.								
_									
19050	19050 Removable Cane Handle Push Bar Not compatible with Stroller Handle Back.								
Endomorph Back Backrest will be narrower than Seat by total of 2x the Offset selected below. Minimum width of Backrest is 12".									
18102	· · · · · · · · · · · · · · · · · · ·								
19212	Headrest Mounting Plate Not compatible with Angle/Height Adjustable Stroller Handle, Cane Handle Back. Not required if mounting to a solid Back.	\$							
19240	Seating Dynamics Dynamic Rocker Back Interface	\$							
	Not compatible with Take-Apart Frame, Fold-down Back, 30° Recline, Standard Upholstery. Only availabe with Stroller Handle - 8° Bend. Finished Back Post Height is 7" taller than selected Back Post Height. Maximim compative Seat Depth is 20". 90° and 98° Seat Angle only.								
Back	Upholstery								
20000	No Back Upholstery								
	Standard Upholstery Not available with Cane Handle Back.	\$							
20418	Short (18" Height) 🔲 20421 Regular (21" Height)								
20450	<b>Tension Adjustable Upholstery</b> Height of Upholstery is 16". Not available with Cane Handle Back.	\$							
	Position of Upholstery Select the desired position of the top of the Upholstery relative to the Seat Pan.								
	17" Back Post 23" Back Post								
	Style 17" 18" 19" 20" 21" 22" 23" 24" 25" Style 17" 18" 19" 20" 21" 22" 23"	24" 25"							
	Short								
	Regular								
	Tension Adj								
Tilt	Activation								
1116 /									
23011	Attendant Tilt only Select trigger mounting location below.  Right Back Post  23012 Left Back Post								
23011									
	Power Tilt 40° tilt range. Includes 2 batteries for off-chair charging. pdgmobility.com/power-tilt	÷							
23400	Standard Power Tilt (113kg/250 lbs Weight Capacity)	\$							
23401	Standard Power Tilt (159kg/350 lbs Weight Capacity) Requires Fixed Frame.  Power Tilt with Manual Tilt Override (113kg/250 lbs Weight Capacity) Allows for instant manual release of tilt in case of power tilt failure.	\$							
23410	Power Tilt with Manual Tilt Override (175kg/250 lbs Weight Capacity)  Allows for instant manual release of tilt in case of power tilt failure.	\$							
	Toggle Switch	•							
Selec	•								
Contraction Switch	rol								
SWILL	Optional for Egg Switch: 23445 Swing Away Mounting Hardware Not compatible with all Headrest makes and models.	\$							
	Specify Headrest to be used:	·							
	Tilt Limit Optional. If no tilt limit is selected, the full tilt range will be available.								
□ 23220	Set at 20° □ 23230 Set at 30° □ 23240 Set at 40°								
Recli	in e								
23310	Reclining Backrest (Manual)	\$							
	30° maximum recline. Not compatible with Cane Handle Back, Fold-down Back. Not available with 22" Seat Depth. Finished Back Post Height is 3" taller than selected Back Post Height.								
Fron	t Rigging								
<b>D</b> 25000	No Front Rigging 25001 Sector Blocks only								
	Easy-Out ** Front Rigging Effortless insertion and removal. No Hanger Bracket remains on frame. pdgmobility.com/easy-out								
□ 25410		\$							
□ 25420	Universal Angle Adjustable (0°-110°) Set at angle: (use increments of 10°)	\$							
	Adjust angle by loosening one bolt. Tool-free leg-length adjustment. Front Rigging can interfere with casters in the 90-110° settings.								



	Swing Away Front Rigging Legacy Design. Not compatible with Easy-Out. Requires pre-tilt of 5°.	
<u> </u>	Swing Away 60°	
<u> </u>	Swing Away 90° Includes 11"-16" Extension Tubes. Not compatible with 8" Casters.	\$
<u> </u>	Swing Away Elevating Legrests Includes Calf Pads.	\$
<u> </u>	1" Offset Hangers for Swing Away	\$
<u> </u>	Standard Plug In 70° Front Rigging Legacy Design. Not compatible with Easy-Out.	
Foot	plates	
26010	Composite Footplates	
<u> </u>	Aluminium Angle Adjustable Footplates	\$
<u> </u>	One Piece Fixed Footplate Available on Plug In Front Rigging only. Requires selection of Composite or Aluminium Angle Adjustable.	\$
<u> </u>	One Piece Flip-up Footplate Requires selection of Composite or Aluminium Angle Adjustable.	\$
☐ 26050	Interlocking Angle Adjustable Footplates Available for Seat Widths up to 21" only.	\$
	menocally migre majustable rootplates - mainsie for seat maths up to 21 only.	7
Foot	rest/Legrest Accessories	
	Calf Pad Not compatible with Gel Padding.	
<b>27012</b>	For Easy-Out TM Front Rigging Includes reinforced premium Calf Pad mount.	\$
<b>27010</b>		\$
□ 27020	Gel Padding Not compatible with Calf Pad or Easy-Out Front Rigging.	\$
	Gel Knee Pad	
□ 27032	For Easy-Out <sup>™</sup> Angle Adjustable Front Rigging	\$
□ 27030	For Swing Away ELR Front Rigging	\$
□ 27040	Length Adjustable Heel Loops	\$
<u> </u>	Bodypoint Padded Calf Strap Sizes greater than 22" are not padded.	\$
Front	t Rigging Extension Tubes	
	Regular Extension Tubes No selection required for 90° Front Rigging	
28010	Short 14"-18" for Easy-Out Front Rigging 13"-17" for Swing Away and Standard Plug In Front Rigging	
28020	Long 18"-24" for Easy-Out Front Rigging 15"-19" for Swing Away and Standard Plug In Front Rigging	\$
2	<b>Lower Leg Length</b> If provided, Front Rigging will be set to this length by PDG. If left blank, the default setting will be used.	
3	Seat Pan to Foot Plates: Measured along the length of the Front Rigging. Consider the height of your Seat Cushion.	
Misc	ellaneous Options	
	One-Arm Drive Available with 22" and 24" Composite Rear Wheels. Minimum 17" STF and 18" STF, respectively.	\$
	Not compatible with Drum Brakes, Quick Release Rear Axles, Pneumatic Tires.	
30010	Installed on Right side	
30012	- 5	
	Spoke Guards Available for 20"-24" Composite Rear Wheels. Made from durable and lightweight aluminium.	\$
□ 30020		
	Stealth Flip Down Abductor Requires Solid Seat Pan.	\$
30060	Small Pad 3"x4"x3"x2" size 🔲 30062 Large Pad 5"x5"x4"x3" size	
30070	·	\$

See next page for more options >

### **Order Form - NZ**





30080	Gel Hip Guides Reduces available Seat Width by 2".	\$						
30090	lip Belt Mount Provides improved mounting options for Bodypoint Hip Belt or other third-party belts.							
	IV Pole	\$						
30110	Installed on Left Side 🔲 30111 Installed on Right Side							
30120	O2 Holder May add to overall width of the Chair. \$							
30150	Ventilator Tray Reduces ground clearance. Chair may be unstable when unoccupied. Minimum Seat Width is 16". \$							
	Not compatible with O2 Holder, Power Tilt, Foot Operated Wheel Locks.							
30152	Ventilator Bracket         Compatible with LTV1 (laptop) ventilator.         \$							
30160	Clear Lap Tray (Slide On) Available for Seat Widths of 17"-22" only. Not compatible with Contour Arm Trough.							
30200	Q'Straint Lap Belt         Model S5-6329-11. For use with WC-19 Transit Tie Down System. 24"-51" Belt Length.         \$							
30222	Wheelchair Backpack Black with PDG Logo. 17"x14" size. \$							
30170	Adhesive Back Hook Strip, 2" x 30" For Cushion mounting.	\$						

О	)	r	d	е	r	- 1	V	0	t	e	S